

SOLYX SimGlas®

SGC-6515 Fluted Glass



Product Details

SGC-6515 Fluted This adhesive polyester film very nicely simulates textured glass. Vertical, crystal-clear fluted lines providing semi-private distortion views. Flutes are 3/16" wide / 0.1875" in between. This dimensionally stable film is 100% UV stabilised, will not discolour nor shrink, and is supplied with a silicone coated liner which protects the clear, pressure-sensitive acrylic adhesive.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SGC-6515
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	58"
Thickness	50 micron
Visible Light Transmission	90%
UV Transmission	1%
Solar Energy Absorbed	28%
Solar Energy Rejected	15%
Shading Coefficient	0.93%
Visible Light Reflectance	7%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

50 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu