

SOLYX SimGlas®

SGV-6608 Frosted Diamond



Product Details

SGV-6608 Frosted Diamond is a durable, polymeric PVC film that is UV stabilized and will not discolour nor shrink. It has a 5mm frosted diamond pattern with 1mm clear spacing and is manufactured with a silicone coated liner which protects the clear, pressure-sensitive acrylic adhesive.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SGV-6608
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	48"
Thickness	127 micron
Shading Coefficient	0.93%
Visible Light Transmission	81%
UV Transmission	70%
Visible Light Reflectance	7%
Solar Heat Transmission	76%
Solar Heat Reflectance	7%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

127 micron Polymeric Vinyl

Adhesive

Clear, Pressure-Sensitive

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu