

SOLYX®

SX-1003 Clear Frosted Squares



Product Details

SX-1003 Clear Frosted Squares 3" x 3" Translucent squares of embossed vinyl film separated by clear lines. Ideal for obscuring direct visibility and allows excellent light transmission.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

| | |
|----------------------------|--------------------|
| Product Code | SX-1003 |
| Film Type | Vinyl |
| Adhesive Type | Pressure-sensitive |
| Usage | Interior |
| Available Roll Width(s) | 48" |
| Thickness | 100 micron |
| Shading Coefficient | 0.93% |
| Visible Light Reflection | 70% |
| Visible Light Transmission | 74% |
| Infra-Red Transmission | 68% |
| UV Transmission | 66% |
| Solar Heat Reflection | 7% |
| Solar Heat Transmission | 76% |

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

100 micron Vinyl

Adhesive

Clear, Pressure-sensitive, 17 – 22 micron

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu