

SOLYX SimGlas®

SX-1254 Reeded Glass



Product Details

SX-1254 Reeded Glass adhesive film simulates real reeded glass. The Bars are 1/2" wide and the pattern direction runs down the length of the roll. The clear glasslike distortion texture provides a semi-privacy view. Often used in restaurants for booth divider privacy.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-1254
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	54"
Thickness	50 micron
Visible Light Transmission	61%
UV Transmission	<1%
UV Rejection	43%
Total Solar Reflectance	8%
Total Solar Absorbance	15%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

50 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu