Specification Sheet







SX-1303 Grey Frost

Product Details

SX-1303 Grey Frost. Frosted, translucent, high-grade, embossed vinyl film. Simulates sand-blasted glass. Ideal for obscuring direct visibility, reducing glare while allowing excellent light transmission.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-1303
Film Type	Polymeric Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	60"
Thickness	100 micron
Visible Light Transmission	27%
UV Transmission	2%
Infra-Red Transmission	45%
Absorption	43%
Total Solar Energy Rejected	62%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior applications have a three (3) year warranty. See warranty information for specific details.

Product Construction

Face Film 100 micron Polymeric Vinyl

Adhesive Clear, Pressure-Sensitive

Release Liner Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel:	+44 (0) 800 970 6366
Email:	sales@glassfilms.eu
Web:	www.glassfilms.eu