Specification Sheet

glassfilms®
decorative | innovative | architectural

SOLYX®

SX-3150 Geometric

Product Details

SX-3150 Geometric is an attractive architectural square geometric pattern with a matte finish and fine transparent lines - perfect for subtle privacy.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-3150
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	60"
Thickness	63 micron
Visible Light Transmission	37%
UV Transmission	21%
Total Solar Energy Rejected	40%
Infra-Red Transmission	39%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film
63 micron PET

Adhesive
Clear, Pressure-Sensitive

Release Liner
Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information
Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu