

SOLYX®

SX-324 Frosted Sparkle



Product Details

Durable, dimensionally stable, translucent film.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-324
Film Type	Vinyl & Polycarbonate
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	48"
Thickness	51 micron
Visible Light Transmission	37%
UV Transmission	10%
Infra-Red Transmission	39%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

51 micron Cast Vinyl

Adhesive

Clear, Pressure-sensitive

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu