

SOLYX®

SX-9100 Chicago



Product Details

SX-9100 Chicago. A modern pattern of short, fragmented, white strokes with clear background. (A derivative of our SXHE-1034 Ice Forest) Excellent distraction film.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®

Specification

| | |
|----------------------------|--------------------|
| Product Code | SX-9100 |
| Film Type | Polyester |
| Adhesive Type | Pressure-sensitive |
| Usage | Interior |
| Available Roll Width(s) | 60" |
| Thickness | 51 micron |
| Visible Light Transmission | 56% |
| UV Transmission | 50% |
| Infra-Red Transmission | 58% |

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

51 micron Polyester

Adhesive

20 micron to 25 micron, Acrylic, Clear, Pressure-sensitive

Release Liner

51 micron Polypropylene, Silicone Coated (Thickness variation +/- 10%)

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu