

## SOLYX®

## SXD-1616 Dots



### Product Details

Translucent White Diagonal Dots: 1/16" dot, 1/16" clear space. Translucent White Dots on optically clear window film providing semi-obscure. (The film is 60" wide however the dot pattern on the film is 59" wide)

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

The product complies with ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	SXD-1616
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	60"
Thickness	51 micron
Shading Coefficient	.93%
Visible Light Reflectance	79%
Visible Light Transmission	85%
UV Transmission	17%
Solar Heat Reflectance	7%
Solar Heat Transmission	76%
Solar Heat Absorption	17%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

51 micron Polyester

#### Adhesive

Adhesive Clear, pressure-sensitive

#### Release Liner

Transparent, Synthetic, Plottable

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)