# **Specification Sheet**







## SXJ-0546 Organic Cotton Gradient

## **Product Details**

SXJ-0546 Organic Cotton Gradient. Simulates muslin or cotton fabric that fades from semi-transparent to clear. An elegant film that provides privacy while still allowing excellent light transmission. The design can be extended at the bottom of this film by using <u>SXJ-</u> 0567 Solid White.

#### **Flammability Rating**

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

## Specification

| Product Code                   | SXJ-0546           |
|--------------------------------|--------------------|
| Film Type                      | Polyester          |
| Adhesive Type                  | Pressure-sensitive |
| Usage                          | Interior           |
| Available Roll Width(s)        | 71″                |
| Thickness                      | 100 micron         |
| Shading Coefficient            | 0.55%              |
| Visible Light Reflection       | 27%                |
| Visible Light Transmission     | 25%                |
| UV Transmission                | 2%                 |
| Infra-Red Transmission         | 70%                |
| Total Solar energy<br>Rejected | 38%                |
| Solar Energy Absorbed          | 25%                |

## **Installation & Warranty**

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

## **Product Construction**

Face Film

100 micron Polyester

| Distribution & Contact Information            |
|---|
| Solvx® Decorative Films are available through |

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

| Adhesive<br>Clear, Pressure-Sensitive | <b>Contact Information</b><br>Glass Films |                      |  |
|---------------------------------------|---|----------------------|--|
| Release Liner                         | Tel:                                      | +44 (0) 800 970 6366 |  |
| Silicone Coated                       | Email:                                    | sales@glassfilms.eu  |  |
|                                       | Web:                                      | www.glassfilms.eu    |  |