

SOLYX®

SXJ-0567 Solid White



Product Details

This film is recommended for use in conjunction with the most opaque area of the 71" white gradient films and 60" high. The films compatible with this film are [SXJ-0541](#), [SXJ-0545](#), [SXJ-0546](#), [SXJ-0547](#), [SXJ-0549](#), [SXJ-0594](#).

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXJ-0567
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	58"
Thickness	100 micron
Shading Coefficient	0.55%
Visible Light Reflection	27%
Visible Light Transmission	4%
UV Transmission	0%
Infra-Red Transmission	6%
Total Solar energy Rejected	38%
Solar Energy Absorbed	25%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

100 micron Polyester

Adhesive

Clear, Pressure-Sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu