

## SOLYX®

## SXJ-0590 Point Gradient



### Product Details

Point Gradient Dot window film graduates in opacity from the bottom of the film to the top. This film may also be installed with the opaque area at the top of the glass fading to clear towards the centre.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	SXJ-0590
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	60"
Thickness	50 micron
Shading Coefficient	0.55%
Visible Light Reflection	27%
Visible Light Transmission	49%
UV Transmission	2%
Infra-Red Transmission	70%
Total Solar energy Rejected	38%
Solar Energy Absorbed	25%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

50 micron Polyester

#### Adhesive

Clear, Pressure-Sensitive

#### Release Liner

Silicone Coated

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)