
# **Specification Sheet**







# SXWF-CM Charcoal Matte

## **Product Details**

SXWF-CM Charcoal Matte. Charcoal frosted polyester film. Translucent effect. Ideal for obscuring direct visibility and allows excellent light transmission.

#### **Flammability Rating**

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.** 

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

# Specification

Product Code	SXWF-CM
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	60"
Thickness	51 micron
Visible Light Transmission	12%
UV Transmission	9%
Solar Energy Absorbed	38%
Solar Heat Reflection	7%
Glare Reduction	35%
U Value	1.14
Visible Light Reflection	9%
Shading Coefficient	0.78

# **Installation & Warranty**

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### **Product Construction**

Face Film 51 micron Polyester

Adhesive Clear, Pressure-sensitive

### Release Liner

Silicone Coated

# **Distribution & Contact Information**

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### **Contact Information**

Glass Films

Tel:	+44 (0) 800 970 6366
Email:	sales@glassfilms.eu
Web:	www.glassfilms.eu