


SOLYX®

SXWF-SM Silver Matte



Product Details

SXWF-SM Silver Matte. Silver/matte frosted polyester translucent effect. Rejects heat and glare. Ideal for obscuring direct visibility and allows excellent light transmission.

Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXWF-SM
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	60"
Thickness	102 micron
Visible Light Transmission	4%
UV Rejection	100%
Total Solar Absorbance	30%
Total Solar Reflectance	57%
Glare Reduction	82%
Total Solar Energy Rejected	79%
Shading Coefficient	0.24

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

51 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366 Email: sales@glassfilms.eu Web: www.qlassfilms.eu