Specification Sheet







SXWF-TWM Transparent White Matte

Product Details

SXWF-TWM Transparent White Matte frosted polyester translucent/transparent effect. Ideal for obscuring 70% visibility and excellent light transmission.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXWF-TWM
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	48", 60"
Thickness	50 micron
Visible Light Transmission	53%
UV Transmission	0%
Infra-Red Transmission	66%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior applications have a three (3) year warranty. See warranty information for specific details.

Product Construction

Face Film

50 micron Polyester

Adhesive

20 to 25 micron, Clear, Acrylic, Pressure-Sensitive

Release Liner

50 micron Polypropylene, Silicone Coated (Thickness variation +/- 10%)

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel:	+44 (0) 800 970 6366
Email:	sales@glassfilms.eu
Web:	www.glassfilms.eu