


SOLYX®

SXWF-WM White Matte



Product Details

SXWF-WM White Matte. White frosted polyester translucent effect. Ideal for obscuring direct visibility and allows excellent light transmission. Better than sandblasted glass.

Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXWF-WM
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Interior or Exterior
Available Roll Width(s)	48", 60"
Thickness	51 micron
Shading Coefficient	0.82
Visible Light Transmission	11%
UV Transmission	<1%
Solar Energy Absorbed	22%
Glare Reduction	38%
Infra-Red Transmission	14%
Total Solar Energy Rejected	58%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

51 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366 Email: sales@glassfilms.eu Web: www.glassfilms.eu