

SOLYX®

SX-C378 Alternating Stripes



Product Details

SX-C378 Alternating Stripes Window Film.
Alternating Etch and Translucent white stripes.
Stripes are 3.5mm wide with a 2mm space.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

| | |
|----------------------------|--------------------|
| Product Code | SX-C378 |
| Film Type | PET |
| Adhesive Type | Pressure-sensitive |
| Usage | Interior |
| Available Roll Width(s) | 48", 60" |
| Thickness | 64 micron |
| Visible Light Transmission | 66% |
| UV Transmission | 47% |
| Infrared Transmission | 72% |

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

PET

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu