

SOLYX®

SX-C390 Black Screen



Product Details

SX-C390 Black Screen: Self-Adhesive film with thin vertical and horizontal black lines forming tiny clear squares. Look simulates screens.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

When applied to glass or plastic surfaces:
Horizontal Burn (Flame Spread) ASTM D-635 inch
Less than 1.0
UL 94 Rating UL Classification V-O
Class A 0 -25 Flame Spread Index 0 -450

Specification

Product Code	SX-C390
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	60"
Thickness	51 micron
Shading Coefficient	.93%
Visible Light Reflection	70%
Visible Light Transmission	30%
Infra-Red Transmission	39%
UV Transmission	24%
Solar Heat Reflection	7%
Solar Heat Transmission	76%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

51 micron Polyester

Adhesive

Clear, Pressure-sensitive – 0.7 – 0.87 mil

Release Liner

38 micron Silicone

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu