Specification Sheet







SXD-4250 DichroFrost

Product Details

A shimmering and beautiful, dichroic frost film, that shifts through a rainbow of colours from a change in light or movement. An excellent privacy film obscuring direct visibility and allowing excellent light transmission. Adhesive backed.

Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXD-4250
Film Type	Vinyl/Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	35"
Thickness	203 micron
Visible Light Transmission	75%
UV Transmission	7%
Infrared Transmission	75%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

152 micron Vinyl/ 51 micron Polyester

Adhesive

Adhesive Clear, pressure-sensitive

Release Liner Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel:	+44 (0) 800 970 6366
Email:	sales@glassfilms.eu
Web:	www.glassfilms.eu