

## SOLYX®

## SXEG-4856 Stone Wall



### Product Details

SXEG-4856 Stone Wall. Textured Stone Wall film giving the effect of real masonry. Provides effective semi privacy. This film is 48" wide.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	SXEG-4856
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	48"
Thickness	51 micron
Visible Light Transmission	65% - 82%
UV Transmission	5%
Total Solar Energy Absorbed	35%
Total Solar Energy Rejected	35%
Reflectance	8%
Shading Coefficient	.95
U Value	1.75

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

51 micron Polyester

#### Adhesive

Clear, Pressure-sensitive, Removable

#### Release Liner

Silicone

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366  
Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)  
Web: [www.glassfilms.eu](http://www.glassfilms.eu)