

SOLYX®

SXEG-4865 Calligraphy



Product Details

SXEG-4865 Calligraphy. Beautifully coloured, stained-glass pattern. Translucent. Excellent light transmission. Pattern is a 48" finished width with a 21" repeat.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXEG-4865
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	48"
Thickness	51 micron
Visible Light Transmission	60%
UV Transmission	25%
Total Solar Energy Absorbed	35%
Total Solar Energy Rejected	35%
Reflectance	0 - 8%
Shading Coefficient	.95
U Value	1.75

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

51 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu