

SOLYX®

SXEG-4868 Oasis



Product Details

SXEG-4868 Oasis. Beautifully coloured, stained-glass pattern. Translucent. Excellent light transmission. Pattern is a 48" finished width with a 21" repeat.

Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

| Product Code | SXEG-4868 |
|--------------------------------|--------------------|
| Film Type | Polyester |
| Adhesive Type | Pressure-sensitive |
| Usage | Interior |
| Available Roll Width(s) | 48" |
| Thickness | 51 micron |
| Visible Light Transmission | 59% |
| UV Transmission | 45% |
| Total Solar Energy Absorbed | 35% |
| Total Solar Energy Rejected | 35% |
| Reflectance | 0-8% |
| Shading Coefficient | .95 |
| U Value | 1.75 |

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

51 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366 Email: sales@glassfilms.eu Web: www.glassfilms.eu