

SOLYX®

SXHK-01 Shoji Screen



Product Details

SXHK-01 Shoji Screen White Opaque Shoji Screen film. Exact representation of Rice Paper. Ideal for obscuring direct visibility allowing subtle light transmission. This film is not suitable for wet conditions.

FOR BATHROOM APPLICATIONS WE HIGHLY RECOMMEND SXWF-WM White Matte.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXHK-01
Film Type	Polyester Fibre & PVC
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Roll Width(s)	36"
Thickness	102 micron
Shading Coefficient	.65
Visible Light Transmission	12%
UV Transmission	4%
Total Solar Energy Absorbed	23%
U Value	1.75
Total Solar Energy Rejected	78%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

102 micron Polyester Fibre and PVC combination

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu