# **Specification Sheet**





## SXHP-2411 White Stripes



## **Product Details**

SXHP-2411 White Stripes 11/16" separated by 1/4" clear lines. Ideal for obscuring semi-direct visibility and allows excellent light transmission.

#### **Flammability Rating**

This product meets **Class B**, **s1**, **d0**, as specified in **BS EN 13501-1:2018**.

Horizontal Burn (Flame Spread) ASTM D-635 inch Less than 1.0 UL 94 Rating UL 94 Classification V-O Class A 0 -25 Flame Spread Index 0 -450 Smoke Developed Index

## Specification

Product Code	SXHP-2411
Film Type	PET
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Roll Width(s)	48"
Thickness	38 micron
Visible Light Transmission	65%
UV Transmission	57%
Infra-Red Transmission	74%
Total Solar Energy Rejected	32%

## **Installation & Warranty**

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

## **Product Construction**

Face Film 38 micron PET

Adhesive Clear, Pressure-sensitive

**Release Liner** Silicone

## **Distribution & Contact Information**

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

www.glassfilms.eu

#### **Contact Information**

Web:

Glass Films	
Tel:	+44 (0) 800 970 6366
Email:	sales@glassfilms.eu