

## SOLYX®

## SXL-1017 Clear Fine Brushed



### Product Details

SXL-1017 Clear Fine Brushed. Brushed, Translucent embossed vinyl film. Ideal for obscuring direct visibility and allows excellent light transmission.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	SXL-1017
Film Type	Vinyl
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Roll Width(s)	60"
Thickness	127 micron
Shading Coefficient	.93%
Visible Light Reflection	70%
Visible Light Transmission	46%
UV Transmission	11%
Solar Heat Reflection	7%
Solar Heat Transmission	76%
Infra-Red Transmission	41%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

127 micron Vinyl

#### Adhesive

Clear, Pressure-sensitive – 0.7 – 0.87 mil

#### Release Liner

Silicone Coated

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)