

## SOLYX®

### SXV-9-1003 Black Gloss



#### Product Details

SXV-9-1003 Black Gloss, cast vinyl film. Suitable for application to Glass and Acrylics. Good for exterior applications.

#### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

#### Specification

Product Code	SXV-9-1003
Film Type	Cast Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	48"
Thickness	50 micron
Visible Light Transmission	2%
UV Transmission	0%
Solar Energy Absorbed	60%
IR Rejection	99%

#### Installation & Warranty

##### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

##### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

#### Product Construction

##### Face Film

50 micron Cast Vinyl

##### Adhesive

Clear, Solvent Acrylic, Pressure-Sensitive

##### Release Liner

Poly, plottable release liner

#### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

##### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)