


SOLYX®

SX-SC463 Axis



Product Details

SX-SC463 Axis Non-Adhesive Static Cling Window Film. Beautiful prismatic cut glass effect privacy film. Fully removeable and reusable.

Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-SC463
Film Type	Polypropylene
Adhesive Type	Non-Adhesive Static Cling
Usage	Interior
Available Roll Width(s)	35"
Thickness	+/- 203 micron
Visible Light Transmission	80%
Infra-Red Transmission	72%
UV Transmission	30%
Absorption	42%
Total Solar Energy Rejected	56%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

203 micron Polypropylene

Adhesive

Non-Adhesive Static Cling

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu