

## SOLYX®

## SX-SC509 Prism Static Cling



### Product Details

SX-SC509 Prism Static Cling: Translucent, colourless embossed vinyl film. Prismatic diamonds. Static-cling, non-adhesive.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	SX-SC509
Film Type	Polypropylene
Adhesive Type	Non-Adhesive Static Cling
Usage	Interior
Available Roll Width(s)	35.5"
Thickness	+/- 203 micron
Visible Light Transmission	63%
Infra-Red Transmission	70%
UV Transmission	29%
Absorption	42%
Total Solar Energy Rejected	56%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

203 micron Polypropylene

#### Adhesive

Non-Adhesive Static Cling

#### Release Liner

Transparent Synthetic

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)