


SOLYX®

SX-SC554 Mystic



Product Details

SX-SC554 Mystic: Non-Adhesive Static Cling window film. Horizontal prismatic waves creating attractive privacy.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-SC554
Film Type	Polypropylene
Adhesive Type	Non-Adhesive Static Cling
Usage	Interior
Available Roll Width(s)	35.5"
Thickness	229 micron
Visible Light Transmission	40%
IR Transmission	37%
UV Transmission	18%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

203 micron Polypropylene

Adhesive

Non-Adhesive Static Cling

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366 Email: sales@glassfilms.eu Web: www.qlassfilms.eu