

## SOLYX®

## SX-1261 Solitude



### Product Details

SX-1261 Solitude is a lightly textured, semi-transparent, polyester film that simulates glass and provides a distorted view and excellent light transmission. This dimensionally stable film is 100% UV stabilized, will not discolor nor shrink, and is supplied with a silicone coated removable liner which protects the clear, pressure-sensitive acrylic adhesive

### Flammability Rating

This product meets Class B, s1, d0, as specified in BS EN 13501-1:2018.

The product complies with ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	SX-1261
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	54"
Thickness	50 micron
Shading Coefficient	.93
Visible Light Transmission	90%
Visible Light Reflectance	7%
UV Transmission	1%
Solar Energy Absorbed	28%
Solar IR Rejected	15%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

50 micron Polyester

#### Adhesive

Clear, Pressure Sensitive

#### Release Liner

Transparent Synthetic

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)