

SOLYX  
UltraCool®

## UltraCool-S1560 15% VLT Silver Window Film



### Product Details

UltraCool-S1560 Heat Rejection Film. UltraCool-S1560 15% VLT Silver reflective window films (78% Heat rejection) set the industry standard as one of the most powerful and economical solar heat rejecting films available while maintaining minimal light reduction. A window film with fantastic solar performance specifications which still provides the preferred appearance for residential applications.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	UltraCool-S3560
Film Type	Polyester
Adhesive Type	Acrylic Pressure-Sensitive
Usage	Interior
Available Roll Width(s)	60"
Thickness	51 micron
Shading Coefficient	.25
Visible Light Reflectance	55.9%
Visible Light Transmission	25%
UV Transmission	<1%
Total Solar Energy Absorbed	36.8%
Total Solar Energy Rejected	78.3%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

51 micron Metalized Polyester

#### Adhesive

Solvent Acrylic, Pressure Sensitive

#### Release Liner

Transparent Synthetic

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)

Web: [www.glassfilms.eu](http://www.glassfilms.eu)