## **Specification Sheet**







# SX-1277 Spun Glass

## **Product Details**

SX-1277 Spun Glass film is a polyester, adhesive, semi-transparent film, simulating real glass. This crosshatch spun design provides good view distortion for privacy.

#### **Flammability Rating**

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.** 

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

## Specification

Product Code	SX-1277
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	54"
Thickness	50 micron
Shading Coefficient	0.93%
Visible Light Transmission	90%
UV Transmission	1%
Visible Light Reflection	7%
Solar Energy Absorbed	28%
Solar IR Energy Rejected	15%

## **Installation & Warranty**

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### **Product Construction**

Face Film 50 micron Polyester

Adhesive Clear, Pressure-sensitive

**Release Liner** Transparent Synthetic

### **Distribution & Contact Information**

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### **Contact Information**

Glass Films

 Tel:
 +44 (0) 800 970 6366

 Email:
 sales@glassfilms.eu

 Web:
 www.glassfilms.eu