

## SOLYX SimGlas®

## SX-1279 Arctic Glass



### Product Details

SX-1279 Arctic Glass film is a polyester, adhesive, semi-transparent film. This film simulates textured Arctic Glass and provides good view distortion for privacy.

### Flammability Rating

This product meets **Class B, s1, d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

### Specification

Product Code	SX-1279
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	54"
Thickness	50 micron
Shading Coefficient	0.93%
Visible Light Transmission	90%
UV Transmission	1%
Visible Light Reflection	7%
Solar Energy Absorbed	28%
Solar IR Energy Rejected	15%

### Installation & Warranty

#### Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

#### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

### Product Construction

#### Face Film

50 micron Polyester

#### Adhesive

Clear, Pressure-sensitive

#### Release Liner

Transparent Synthetic

### Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

#### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366  
Email: [sales@glassfilms.eu](mailto:sales@glassfilms.eu)  
Web: [www.glassfilms.eu](http://www.glassfilms.eu)