Specification Sheet







SX-1281 Crystal Weave 1/2"

Product Details

SX-1281 Crystal Weave 1/2" is designed to resemble cut crystal in an elegant weave configuration. The pattern consists of blocks, each measuring ½ inch.

Flammability Rating

This product meets **Class B**, **s1**, **d0**, as specified in **BS EN 13501-1:2018**.

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-1281
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	54"
Thickness	50 micron
Visible Light Transmission	92%
UV Transmission	<1%
UV Rejection	98%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

Product Construction

Face Film

50 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films	
Tel:	+44 (0) 800 970 6366
Email:	sales@glassfilms.eu
Web:	www.glassfilms.eu