Specification Sheet

SOLYX®

BSF-DB35 Solar Bird Safety Film



Product Details

BSF-DB25 Solar Bird Safety Film is a durable, heat rejecting film with a tinted finish. The product is an outside weatherable, scratch resistant film with a pattern of ¼" colourless etch dots separated by 2" clear spacing. Recommended to exterior glass only and is ideal for residential or commercial applications.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	BSF-DB35
Film Type	Polyester
Adhesive Type	Clear, Pressure Sensitive
Usage	Exterior
Available Roll Width(s)	60"
Thickness	100 micron
Shading Coefficient	.41
Visible Light Reflectance	24%
Visible Light Transmission	34%
UV Transmission	<1%
Total Solar Energy Absorbed	41%
Total Solar Energy rejected	65%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of three (3) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

100 micron Polyester

Adhesive

Clear, Pressure Sensitive

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.