Specification Sheet

SOLYX SimGlas®

SGD-6007 Gridlock



Product Details

SGD-6007 Gridlock is a durable, dimensionally stable, translucent film with a semi-transparent interlocking 3/4" square pattern. It is made of polyester and has a silicone liner which protects the clear, pressure-sensitive acrylic adhesive.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SGD-6007
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	58"
Thickness	50 micron
Visible Light Transmission	82%
UV Transmission	5%
Visible Light Reflectance	79%
Shading Coefficient	0.93%
Solar Heat Reflectance	7%
Solar Heat Transmission	76%
Solar Heat Absorption	17%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

50 micron Polyester

Adhesive

Adhesive Clear, Pressure-Sensitive

Release Liner

Transparent, Synthetic, Plottable

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.