
Specification Sheet

SOLYX UltraGreen®

SGD-6015-UG Vienta



Product Details

SGD-6015-UG Vienta is a durable, dimensionally stable, Dusted Window Film with a semi-clear curving line pattern reminiscent of mid-century modern design. Perfect for attractive privacy with moderate light transmission. Manufactured with a plottable liner, it is recommended for application to interior glass, and is ideal for semi-privacy, decorative, or architectural applications.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**
This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SGD-6015-UG
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	58”
Thickness	50 micron
Visible Light Transmission	58%
UV Transmission	1%
UV Rejection	99%
IR Rejection	40%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

Polyester

Adhesive

Removable, Pressure-Sensitive

Release Liner

Synthetic, Plottable

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.