Specification Sheet

SOLYX UltraGreen®

SX-1255-UG 1” Reeded Glass



Product Details

SX-1255-UG 1" Reeded Glass adhesive film simulates real reeded glass. Bands are 1" wide and band direction is vertical, down the length of the roll. Recommended for application to interior glass, single- or double-pane, it is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-1255-UG
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	30”, 60”
Thickness	50 micron
Visible Light Transmission	70%
UV Transmission	<1%
UV Rejection	98%
Total Solar Reflectance	8%
Total Solar Absorbance	15%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

50 micron Polyester

Adhesive

Clear, Pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.