Specification Sheet

SOLYX®

SX-1477 Cut Glass Drops



Product Details

SX-1477 Cut Glass Drops. This film has a self-stick pressure sensitive adhesive with protective clear liner, an excellent privacy film obscuring direct visibility and allowing excellent light transmission.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-1477
Film Type	Polypropylene
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	48”
Thickness	203 micron
Visible Light Transmission	84%
UV Transmission	37%
IR Transmission	76%
Absorption	42%
Total Solar Energy Rejected	56%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

203 micron Polypropylene

Adhesive

Clear, Pressure-Sensitive

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.