Specification Sheet

SOLYX®

SX-1544 Rain Glass



Product Details

Clear like glass embossed vinyl privacy film simulating Textured Rain Glass. Semi-Obscures direct visibility. This is the adhesive version of the static cling Rain Glass SX-SC544) Note: This film is designed to be viewed through the film from the installed surface.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-1544
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	24”, 48”
Thickness	203 micron
Visible Light Reflection	6%
Visible Light Transmission	84%
UV Transmission	28%
Infra-Red Transmission	84%
Solar Absorption	32%
Total Solar Energy Rejected	42%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

203 micron Vinyl

Adhesive

Clear, pressure-sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.