Specification Sheet

SOLYX®

SX-3006 White Frosted Mini Blind



Product Details

SX-3006 White Frosted Mini Blind White 3/4" horizontal lines fading to clear on frosted embossed vinyl. Good Privacy! Ideal for obscuring direct visibility and allows excellent light transmission.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-3006
Film Type	Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	59”
Thickness	127 micron
Shading Coefficient	0.93%
Visible Light Reflection	70%
Visible Light Transmission	36%
UV Transmission	1%
Solar Heat Reflection	7%
Solar Heat Transmission	76%
Infra-Red Transmission	42%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

127 micron Polymeric Vinyl

Adhesive

Clear, Pressure-Sensitive, 0.7 – 0.87 mil

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.