Specification Sheet

SOLYX®

SX-3141 Dusted Leaf



Product Details

SX-3141 Dusted Leaf. A soft tone, effective privacy film with a good light transmission. Recommended for application to interior and exterior glass and is ideal for decorative or architectural applications.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-3141
Film Type	PET
Adhesive Type	Pressure-sensitive
Usage	Interior & Exterior
Available Roll Width(s)	48", 59.75"
Thickness	63 micron
Shading Coefficient	0.82%
Visible Light Transmission	23%
UV Transmission	3%
Solar energy absorbed	22%
Total Solar Energy Rejected	40%
Infra-Red Transmission	37%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer's installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior installations have a three (3) year warranty. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

63 micron PET

Adhesive

Clear, Pressure-Sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.