Specification Sheet

SOLYX®

SX-5033 Matte Spring Buds



Product Details

Our White Spring Buds pattern (SX-5020) on a matte finish background. Subtle privacy, good light transmission, polyester film with adhesive and clear protective liner.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-5033
Film Type	Polyester
Adhesive Type	Pressure-Sensitive
Usage	Interior & Exterior
Available Roll Width(s)	60”
Thickness	51 micron
Visible Light Transmission	35%
UV Transmission	17%
Infra-Red Transmission	31%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

50 micron Polyester

Adhesive

20 to 25 micron, Clear, Acrylic, Pressure-sensitive

Release Liner

51 micron Polypropylene, Silicone Coated
(Thickness variation +/- 10%)

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.