Specification Sheet

SOLYX UltraGreen®

SX-8783-UG Eco Sand Blast



Product Details

SX-8783-UG Eco Sand Blast is a translucent, lightly textured film made from durable, dimensionally stable polycarbonate. Manufactured with a silicone coated liner which protects the clear pressure-sensitive adhesive, it is recommended for application to glass, acrylic and polycarbonate sheeting. This film is ideal for privacy, decorative or architectural applications.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-8783-UG
Film Type	Polycarbonate
Adhesive Type	Pressure-Sensitive
Usage	Interior
Available Roll Width(s)	54”
Thickness	76 micron
Visible Light Transmission	54%
UV Transmission	23%
Infrared Transmission	48%
Total Solar Absorption	42%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

76 micron Polycarbonate

Adhesive

Removable, Pressure-sensitive

Release Liner

38 micron Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.