Specification Sheet

SOLYX®

SX-SC679 Florentine



Product Details

SX-SC679 Florentine: Static cling, non-adhesive window film. Simulates Florentine glass pattern. Allows plenty of light through while providing decorative privacy.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX-SC679
Film Type	Polypropylene
Adhesive Type	Non-Adhesive Static Cling
Usage	Interior
Available Roll Width(s)	24”
Thickness	304 micron
Visible Light Transmission	57%
Infra-Red Transmission	54%
UV Transmission	33%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

Polypropylene

Adhesive

Non-Adhesive Static Cling

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.