Specification Sheet

SOLYX®

SX3-314 Acid Etch



Product Details

SOLYX: Acid Etch. Acid Etch gives the uniform appearance of acid etched glass with a soft frosted appearance.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SX3-314
Film Type	Vinyl
Adhesive Type	Pressure-Sensitive
Usage	Interior or Exterior
Available Roll Width(s)	54”, 60”
Thickness	76 micron
Visible Light Transmission	78%
Infra-Red Transmission	79%
UV Transmission	22%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. Exterior applications have a three (3) year warranty. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

76 micron Vinyl

Adhesive

Water-Based Acrylic, Clear, Pressure-Sensitive
(Note: Adhesive will whiten when installed with water solution and clears once cured.)

Release Liner

Paper on all widths

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.