Specification Sheet

SOLYX®

SXD-4220 DichroGeo



Product Details

A shimmering and beautiful, dichroic cut glass film, that shifts through a rainbow of colours from a change in light or movement. An excellent privacy film obscuring direct visibility and allowing excellent light transmission. Adhesive backed.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

The product was tested according to ASTM E84 and is classified as Class A, as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXD-4220
Film Type	Vinyl/Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	35”
Thickness	305 micron
Visible Light Transmission	75%
UV Transmission	7%
Infrared Transmission	75%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

254 micron Vinyl/ 51 micron Polyester

Adhesive

Adhesive Clear, pressure-sensitive

Release Liner

Transparent Synthetic

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.