# Specification Sheet

SOLYX®

# SXJ-0549 Variable Lines Gradient



## Product Details

A beautiful gradient design with varying widths of vertical stripes, fading from solid white to clear.

### Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

## Specification

| | |
|---|---|
| **Product Code** | SXJ-0549 |
| **Film Type** | Polyester |
| **Adhesive Type** | Pressure-sensitive |
| **Usage** | Interior |
| **Available Roll Width(s)** | 71” |
| **Thickness** | 100 micron |
| **Shading Coefficient** | 0.55% |
| **Visible Light Reflection** | 27% |
| **Visible Light Transmission** | 42% |
| **UV Transmission** | 2% |
| **Infra-Red Transmission** | 70% |
| **Total Solar energy Rejected** | 38% |
| **Solar Energy Absorbed** | 25% |

## Installation & Warranty

### Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

### Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

## Product Construction

### Face Film

100 micron Polyester

### Adhesive

Clear, Pressure-Sensitive

### Release Liner

Silicone Coated

## Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

### Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

*Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.*