Specification Sheet

SOLYX®

SXJ-0577 Dual Cloud Gradient 72”



Product Details

SXJ-0577 Dual Cloud Gradient 72” is a frosted polyester film with a simple feathered fade gradient from eggshell white to clear from the centre up and down. This durable film is designed for application to interior glass, single- or double-pane, and exterior facing glass. It is ideal for privacy, decorative, or architectural applications.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXJ-0577
Film Type	Polyester
Adhesive Type	Pressure-sensitive
Usage	Interior
Available Roll Width(s)	72”
Thickness	100 micron
Shading Coefficient	0.55%
Visible Light Transmission	28%
UV Transmission	2%
Infra-Red Transmission	70%
Total Solar energy Rejected	38%
Solar Energy Absorbed	25%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

100 micron Polyester

Adhesive

Clear, Pressure-Sensitive

Release Liner

Silicone Coated

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366
Email: sales@glassfilms.eu
Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.