
Specification Sheet

SOLYX®

SXV-9-1003 Black Gloss



Product Details

SXV-9-1003 Black Gloss, cast vinyl film. Suitable for application to Glass and Acrylics. Good for exterior applications.

Flammability Rating

This product meets **Class B, s1, d0,** as specified in **BS EN 13501-1:2018.**

This product meets ASTM E84 and is classified as Class A as defined in NFPA 101, Life Safety Code®.

Specification

Product Code	SXV-9-1003
Film Type	Cast Vinyl
Adhesive Type	Pressure-sensitive
Usage	Interior or Exterior
Available Roll Width(s)	48”
Thickness	50 micron
Visible Light Transmission	2%
UV Transmission	0%
Solar Energy Absorbed	60%
IR Rejection	99%

Installation & Warranty

Installation

Installation should be in accordance with the manufacturer’s installation instructions. This film is applied using the same methods used for installing window films.

Warranty

This product will be free from defects in material and manufacture for a period of five (5) years from the date of installation. See warranty information for specific details.

To ensure that **Genuine Solyx®** products have been installed, proof of a valid invoice number is required to validate your warranty. Scan the QR code below or visit www.glassfilms.eu/validate to validate.

Product Construction

Face Film

50 micron Cast Vinyl

Adhesive

Clear, Solvent Acrylic, Pressure-Sensitive

Release Liner

Poly, plottable release liner

Distribution & Contact Information

Solyx® Decorative Films are available through authorised window film installers and signage companies, or directly from Glass Films.

Contact Information

Glass Films

Tel: +44 (0) 800 970 6366

Email: sales@glassfilms.eu

Web: www.glassfilms.eu

Solyx® & Simglas® are trademarks of Decorative Films LLC. © Glass Films 2022, All Rights Reserved.